Halloween Experience 2017: Dungeon of the Doomed

SCENE C/D: GUILLOTINE, VICTIM AND OPERATOR


SEPTEMBER 2017, JAMES BULLOCK


Included are sketches showing the pieces required for assembly of the guillotine prop. Discussed also is the frame for movement of the 'victim' figure.


The guillotine was constructed using CLS timber for the frame and MDF for the lunette. The blade was also made from MDF and sprayed with a metallic silver paint. The frame comprised two pieces of timber spaced apart with full-length MDF pieces, to provide a 'slot' in which the blade could slide vertically.

from top Joseph THICK BACK PIECE DISCARD EXTEND TO HAVE RETT STY. THICK ADONT PIECE 680 MM PLADE GOES BELIND RETT. goomer peces top to bottom figure 15 the print. 50 ... 1900mm. 1200 700 1500 220 400 45W


from the BBSE








part stack to disquise



THIS CAN BE CUT TO FET MANUALLY.

MADE OUT OF BATOM / B & Q NARROW.



GWLOTTAL TOTA LIDTH \$00MM MONT Top PLADE WIDTH GODMAN SOUND.
680. BOBASTONERIAD.
TIL 9mm. BACK K= Dant 6/ans

INTERNALLI

lap of bam/soft pads use there fore and sacr Blq Sutans gradiente for from less smuld be stoop. yours long. X b. coleally. Sig piece of floor town Hung fort pere is

Myer fage like to

Podows

Insche of

Soles, to


crease anothe

Mm or so

of a gap

for losse

faling Stock



LAYER 3+4

